

# 1430/3430

### STANDARD FEATURES

- **Model 1430** - Fail-secure  
**Model 3430** - Fail-safe
- ANSI/BHMA A 156.5 (1 1/4" x 4 7/8"), for use with cylindrical and mortise locksets
- Stainless steel, corrosion-resistant faceplate, suitable for hollow metal, aluminum or wood frames, fits cutout specification A 115.1 (with slight jamb modification)
- Keeper depth - 5/8" maximum latch projection possible with 1/8" door/frame clearance - 3/4" Keeper opening - 3/8" below center line
- **Handed - please specify RH or LH**
- Limited warranty - 36 months



### SPECIFICATION

<b>TAMPER STRENGTH</b>	1700 LB (765 KG)	
<b>VOLTAGE</b>	1430-01 RH	8-16 VAC/3-6 VDC
	1430-01 LH	8-16 VAC/3-6 VDC
	1430-05 RH	12 VAC/VDC
	1430-05 LH	12 VAC/VDC
	1430-08 RH	24 VAC/VDC
	1430-08 LH	24 VAC/VDC
	3430-06 RH	12 VDC
	3430-06 LH	12 VDC
	3430-09 RH	24 VDC
3430-09 LH	24 VDC	
<b>FINISH</b>	US32D, US3 (plated) or US10B	

### SPECIFICATION DETAILS

