

1470B/3470B

STANDARD FEATURES

- **Model 1470** - Fail-secure
Model 3470 - Fail-safe
- Faceplate size 1 3/8" x 9"
- Stainless steel, corrosion-resistant faceplate, suitable for hollow metal, aluminum or wood frames
- Keeper depth - 5/8" maximum latch projection possible with 1/8" door/frame clearance - 3/4" Keeper opening starts at center line
- Cutout for deadbold (Specify 1470B-LH or 1470B-RH, 3470B-LH or 3470B-RH)
- Fully tamper proof horizontal adjustment
- 2" jamb modification
- Limited warranty - 36 months



SPECIFICATION

TAMPER STRENGTH	1700 LB (765 KG)
VOLTAGE	1470-01B/RH 8-16 VAC/3-6 VDC 1470-01B/LH 8-16 VAC/3-6 VDC 1470-05B/RH 12 VAC/VDC 1470-05B/LH 12 VAC/VDC 1470-08B/RH 24 VAC/VDC 1470-08B/LH 24 VAC/VDC 3470-06B/LH 12 VDC 3470-06B/RH 12 VDC 3470-09B/LH 24 VDC 3470-09B/RH 24 VDC
FINISH	US32D, US3 (plated) or US10B

SPECIFICATION DETAILS

