

1701

STANDARD FEATURES

- Fail-secure, faceplate size 1 1/4" x 5 7/8"
- Steel faceplate, suitable for wood frames
- Adjustable keeper, depth - 1/2" max latch projection possible with 1/8" door/frame clearance - 3/4"
- Limited warranty - 36 months

SPECIFICATION

TAMPER STRENGTH	1000 LB (454 KG)
VOLTAGE	1701-01 8-16 VAC/3-6 VDC 1701-05 12 VAC/VDC 1701-07 24 VAC/VDC 1701-08 24 VDC
FINISH	US26D, or US4



1702

STANDARD FEATURES

- Fail-secure, faceplate size 1 1/4" x 4 7/8"
- Anodized aluminum ANSI size faceplate, suitable for hollow metal, aluminum or wood frames
- Adjustable keeper, depth - 1/2" max latch projection possible with 1/8" door/frame clearance - 3/4"
- Reversible - non-handed
- Limited warranty - 36 months

SPECIFICATION

TAMPER STRENGTH	1000 LB (454 KG)
VOLTAGE	1702-01 8-16 VAC/3-6 VDC 1702-05 12 VAC/VDC 1702-07 24 VAC/VDC 1702-08 24 VDC
FINISH	US28, US4 or US10B