


ELECTROMAGNETS


8512-DE

STANDARD FEATURES


- Easy installation with keyhole mounting "slides left to right"
- Dual voltage 12/24 VDC field selectable
- Selectable Delayed Egress cycles: 15 or 30 seconds
- Selectable nuisance delay egress: 0~3 seconds
- Fail alarm: may be released upon activation of fire alarm
- Bond sensor feature for remote monitoring
- Optional remote alarm
- Fail-safe: releases instantly when power is disconnected. No residual magnetism



OPTIONAL REMOTE ALARM



APPLICATIONS



OUTSWING



INSWING

SPECIFICATION

MODELS	HOLDING FORCE	STANDARD FEATURE	CURRENT DRAW	DIMENSIONS
8512-DE	1200 LB	Delay Degress	500 mA/12 VDC 250 mA/24 VDC	Magnet: 10 1/2" x 1 9/16" x 2 11/16" Armature Plate: 7 1/4" x 5/8" x 2 3/8"

RECOMMENDED ACCESSORIES

MODELS	DESCRIPTION	MODELS	DESCRIPTION
9500X36	Micro-Switch Bar US28	10318	16" Door Cord, 5/16" Inside diameter
SIGN-DE 15SEC	Delayed Egress Sign	10320HD US28	Heavy Duty Stainless Steel Door Cord

ELECTROMAGNETS

ELECTRIC STRIKES

EXIT DEVICES

MISC. ACCESS CONTROL