



MAGNETIC LOCK SOLUTIONS

Quality, Commitment, Expertise Since 1980

ROFU Security International Corporation

10029 South Tacoma Way, Suite E11 - Lakewood, WA 98499 - (253)922-1828 - www.ROFU.com - OrderEntry@ROFU.com

8000 Series: Shear Locks

- Compact Locks Designed for Dual Swinging Doors

8100 Series: Full Length Maglocks

- 45" & 96" in Length

8106 Series: Handle Bar Maglocks

- Door Handle: Hidden Magnet Design

8400 Series: Mini & Micro Maglocks

- 600LB & 300LB Maglocks for Top/Front, Surface & Mortise Installation

8500 Series: Entry Level Keyhole Mounting

- US28 & US40
- Optional Delayed Egress Feature
- Oklahoma City Special

8600 Series: Top of The Line Slide Mounting

- 600, 800, 1200LBS, & Double Maglocks, UL listed

8700 Series: Outdoor Maglocks

- 600LB & 1200LB Maglocks, Weatherproof, UL listed

8900 Series: Magnetic Door Holders

- Flush, Wall, & Floor Mount

ACCESSORIES:

- L-Brackets
- Z-Brackets
- U-Brackets
- Spacers
- Filler Plates
- Angle Brackets
- Armature Mounting Brackets
- Armature Housing



8035



8106-HD



8606-BD



8712FT



8900

Optional Features:

- DE = Delayed Egress
- B = Bond Sensor
- D = Door Status
- RD = Relock Time Delay
- LC = Economy Line
- FF = Full Length
- HD = Handle Bar
- FT = Face, Surface, and Sliding
- F = Front Installation
- S = Surface Installation
- M = Mortise Installation

Standard Features:

- Fail Safe- releases Instantly when power is disconnected
- Built-In MOV Spike & Surge Protection
- No Residual Magnetism
- Fail Alarm- May Be Released Upon Activation of Alarm
- 12/24 VDC Selectable (except 8403 models)
- 12/24 VDC/VAC Door Holders

HOW TO ORDER

EX 8 6 1 2 - B D 8 5 1 2 - 2 - B

□
□
□
|

Series Holding force Features Double Door Maglock